

MOUNTING ADHESIVE A 10

PRODUCT

It is manufactured from synthetic resins and high-quality neoprene rubber with the addition of modifiers, fillers and improvers.

APPLICATION

For gluing wood and wood-based materials, rubber, glass, metal, PVC, ceramic tiles in different combinations, for different substrates.

ATTRIBUTES

- easy to use
- bacteriostatic
- it has a very good adhesion to all types of floors used in construction
- high level of tikotropy
- it produces a highly plastic weld
- weather resistant

TECHNICAL DATA

Lp.	Tested attribute	Requirements
1.	Adhesive 's colour	beige
2.	Weld's colour	beige
3.	Dry mass	65% 3
4.	Density	approx. 1,20 g/cm ³
5.	Open time	approx. 6 min
6.	Weld's breaking resilience	min. 2,5 MPa after 1 days min. 3,5 MPa after 3 days

APPLICATION ADVICES

Apply the adhesive spot-on to a clean surface, and merge the bonded parts, then disconnect, allow the solvent evaporate (approximately 3 minutes) and remerge pressing uniformly.

The ambient temperature, the glue and the adhesive materials must be 15–25 degrees and a relative humidity of air 50–80%. Ventilate the room when gluing or after working with the glue.

WARNING

This adhesive is flammable.

Clean freshly soiled surfaces with acetone. After drying, remove mechanically.

STORAGE

Store in original packaging, in a dry place. Do not store directly next to heat sources.

PACKAGING

Available in cartouches.